

LANDLORDS CHECKS FOR CHANGE OF TENANT			
Property		Landlord:-	
FIRE PROTECTION			
Location	Replacement Date	Battery Date	Test Operation
Some smoke detectors either have an expiry or a manufactured date marked on the side or inside beside the battery . Smoke detectors should be replaced after 10 years of manufacture. Also may be prudent and cost effective to replace the battery every 2 years with good quality long life batteries.			
CO2 Protection			
Location	Expiry Date	Battery Date	Test Operation
It may be prudent and cost effective to replace the batteries every 2 years with good quality long life batteries			
RCD Safety Breaker Checks			
RCD 1 (A Right hand side)		RCD 2 (B Left hand side)	
Test Button		Test Button	
The test on these breakers should be operated quarterly and some properties may only have one RCD			
Legionella Checks			
Hot water temperature after 2 minutes	oC	>50oC	Yes / No
Cold water temperature after 2 minutes	oC	< 20oC	Yes / No
These checks should be completed using a BS thermometer and a stopwatch and test should be complete on the taps furthest away from the combi boiler for hot water check and Main stopcock for the cold water check			
Shower head checks			
Shower location		Hose and head cleaned Yes / No	
Shower location		Hose and head cleaned Yes / No	
Shower head and hose should be disconnected from the shower and steeped in a bucket of cold water with a bleach solution and left for 10-15 minutes.			
Vacant property flush through cycle			
Length of period of empty property			
Date of flushing			
Entry date of new tenants			
Flushing should commence at the taps furthest away from the combi boiler and the cold water stopcock. It also may be prudent at the same time to record the water temperatures as per Legionella checks			
Note:-			
Print Name		Signature	Date